
TECHNICAL DATA SHEET **MC 90 - IAP-H90 - G74B**
PRODUCT CODE: **I02920**

Facestock: MC 90

White, semi-gloss, machine coated paper.
Suitable for a wide range of promotional, industrial, logistic and food label applications.
Can be printed with U.V. inks, thermal transfer, cold and hot foil.

Basis weight:	90	gr/m ²	ISO 536
Thickness:	75	µm	ISO 534

Adhesive: IAP-H90

General purpose, permanent rubber based adhesive, providing high performance for the industrial labelling.
Allows good adhesion on most of the surfaces, even those non-polar and difficult.

Tack:	> 12	N/25mm	FTM9 (Glass)
Peel (20 min.):	> 18	N/25mm	FTM1 (Glass)
Cohesion:	Medium		FTM8 (Inox)

Supporto: G74B

Carta glassine supercalandrata bianca

Grammatura:	74	gr/m ²	ISO 536
Spessore:	64	µm	ISO 534
Trasparenza:	> 45	%	DIN 53147

This product is made from certified papers FSC® - Lic. C164660 - Cert. n° INT-COC-001611

Additional information:

We recommend labels always facing out-side in the roll.

Adhesion values make reference to tests on clean and dry glass surface, at standard room conditions of 23°C and 50% R.H. Keep the product at constant room conditions of approximately 20-25 °C and 40-50% R.H. (FINAT indication), avoiding exposition to heat and direct sunlight.

Only the products indicated as such in this document are FSC® certified.