
TECHNICAL DATA SHEET **MC GREASEPROOF - IAP-H90 - G62A**
PRODUCT CODE: **I02970**



Facestock: MC GREASEPROOF

White, semi-gloss, machine coated paper with treatment resistant to oil and greases.
Suitable for olive oil labels and other labels intended for food packaging, where contact with oil and greases is expected.
Can be printed with U.V. inks, thermal transfer, cold and hot foil.

Basis weight:	80	gr/m ²	ISO 536
Thickness:	72	µm	ISO 534

Adhesive: IAP-H90

General purpose, permanent rubber based adhesive, providing high performance for the industrial labelling.
Allows good adhesion on most of the surfaces, even those non-polar and difficult.

Tack:	> 12	N/25mm	FTM9 (Glass)
Peel (20 min.):	> 18	N/25mm	FTM1 (Glass)
Cohesion:	Medium		FTM8 (Inox)

Liner: G62A

Yellow supecalandered glassine paper

Basis weight:	61	gr/m ²	ISO 536
Thickness:	54	µm	ISO 534
Transparency:	> 45	%	DIN 53147

This product is made from certified papers FSC[®] - Lic. C164660 - Cert. n° INT-COC-001611

Additional information:

We recommend labels always facing out-side in the roll.

Adhesion values make reference to tests on clean and dry glass surface, at standard room conditions of 23°C and 50% R.H. Keep the product at constant room conditions of approximately 20-25 °C and 40-50% R.H. (FINAT indication), avoiding exposition to heat and direct sunlight.

Only the products indicated as such in this document are FSC[®] certified.